



## CRL HYDRAULIC 5W-20 MG FLUID

### MULTI-GRADE HYDRAULIC FLUID

**CRL HYDRAULIC MG 5W-20** is a multi-grade anti-wear hydraulic fluid. It has been designed for year-round service in mobile equipment operating at very low or widely varying ambient temperatures. It is recommended for use in mobile hydraulic equipment, including cherry pickers, backhoes, shovels, hydraulic cranes and extension ladders. It can be used in stationary hydraulic equipment operating at abnormally low temperatures. MG 5W-20 provides excellent lubricity and wear protection, oxidation and corrosion protection and detergency for system cleanliness. Meets or exceeds leading pump and system manufacturers specifications such as Delaval, Denison, Dynex, Moog, Racine, Rexroth, Sundstrand, Towler, Vickers, and U.S. Steel.

### TYPICALS

Product Code: 405

Viscosity, cSt @ 40 °C	47.0
Viscosity, cSt @ 100 °C	7.80
Viscosity, SuS @ 100°F.....	236
Viscosity, SuS @210°F.....	50.8
Flash Point COC, ° F	360
Viscosity Index	135
Pour Point, ° F	-45
Gravity, ° API	31.4
Acid #, ASTM D664.....	0.8
Copper Corrosion, D130.....	1A
Foam, D892.....	Pass
Dielectric Strength, D877, Kv.....	35+
Zinc, %wt.....	0.04
Oxidation Stability, Hrs D-943.....	5000